

Description

- USB-RS485 converter for SS 02 series
- USB 2.0 full speed device
- Virtual comport drivers
- Windows XP, 7, 8, 10 and 11 compatible
- Modbus capable



The USB485-CPT/22-300 is a 2 wire RS485 converter with automatic receive / transmit switching with a cable connection for easy installation in screw terminals.

The USB485-CPT/22-300 has a 2,5 kV isolation barrier that ensures a high quality electrical separation between the PC and remote

device, thus offering excellent protection of the PC if the remote device should fail.

Just connect it and install the drivers and use it like any other comport in the PC.

Comport Specifications

| | |
|-------------|--|
| Baudrates | 300, 600, 1200, 1800, 2400, 4800, 7200, 9600, 14400, 19200, 38400, 57600, 115200, 230400, 460800, 921600 Bps |
| Startbits | 1 |
| Databits | 7, 8 |
| Parity | Non |
| Stopbits | 1, 2 |
| Flowcontrol | Autoswitching |
| Buffers | 128 bytes Rx and 256 bytes Tx |

RS485 Data

| | |
|----------------------|-----------|
| Nodes | 256 |
| ESD protection | +/- 15 kV |
| Termination resistor | No |
| Failsafe | Yes |

Hardware Details

| | |
|-----------------------|-------------------------------|
| Connection | 3 m screened cable |
| Visual indicators | 2 (Tx and Rx) |
| Speed | Up to 1 Mbps |
| Isolation voltage | 2,500 Vrms / 1 minute |
| Power | Powered from the PCs USB port |
| Operating Temperature | 0 to +70 °C |


RS485 Connections

| | |
|-----|-------|
| D+ | Green |
| D- | Brown |
| Gnd | White |

Available Type

| | |
|-----------------|-------------------|
| Order Reference | USB485-CPT/22-300 |
|-----------------|-------------------|

Dimensions and Descriptions



(Units in mm)

Telco reserves the right to change specifications without notice.